

PRODUCT DATA SHEET

Sika® Separol® GU

Oil-based shutter release agent

DESCRIPTION

Sika® Separol® GU is an oil based release agent formulated to provide easy release properties to formwork and a high quality surface finish.

USES

Sika® Separol® GU, when applied to steel, plastic or timber formwork allows clean, fast and easy striking.

CHARACTERISTICS / ADVANTAGES

Sika® Separol® GU provides the following beneficial properties:

- Suitable for use on wood, metals and plastic
- Allows clean, easy striking
- Improved finish for fair faced concrete
- Reduces concrete contamination
- Economical coverage rates

PRODUCT INFORMATION

| | |
|----------------------------|--|
| Composition | Oil based agent |
| Packaging | 25 and 200 litre drums 1000 litre IBC |
| Appearance / Colour | Brownish yellow liquid |
| Shelf life | 12 months from date of production |
| Storage conditions | Store properly in original unopened, undamaged, sealed packaging. Protect from frost, direct sunlight and contamination. Opened units should be stored closed. |
| Density | Approximately 0.85 kg/litre |
| Consumption | Timber : <ul style="list-style-type: none"> ▪ approx. 25 sq. meters per litre depending on porosity. Steel or plastic: <ul style="list-style-type: none"> ▪ approx. 50 sq. meters per litre depending on surface texture and porosity. |

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

APPLICATION

Thin layer thickness

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA KENYA LIMITED

Semco Industrial Park Office Block
P.O Box 38645-00623
Parklands, Nairobi, Kenya
Phone: +254 (0)20234900
Mobile: +254 (0) 711140234
web: ken.sika.com